

Model: DSMS-48GPP-4XF



4*10G SFP+ Uplink 48 Port Gigabit PoE Web Smart Switch



Model	DSMS-48GPP-4XF
Product name	4*10G SFP+ Uplink 48 Port Gigabit PoE Web Smart Switch
Fixed Port	48*10/100/1000Base-TX PoE RJ45 (Data+power) 4*1G/10G SFP+
Reset Key	1
Switch function	1: DUMP/WEB on/off (enable/disable web management) 2: Port isolation on/off 3: PoE watchdog on/off
PoE Port	1-2 port supports PoE IEEE 802.3af/at/PoE++/BT MAX 90W 3-48 port supports PoE IEEE 802.3af/at each port 30W
PoE Total Power	≤ 800W
Cache	12M
Bandwidth	256Gbps
Packet Forwarding	131Mpps
MAC Address	16K
Network Protocol	IEEE 802.3、IEEE 802.3 i、IEEE 802.3u、IEEE 802.3ab、IEEE 802.3 z， IEEE 802.3x IEEE802.3af/at/PoE++/BT
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward (full wire speed)
Transmission Distance	10BASE-T : Cat3,4,5 UTP (≤ 250 meter) 100BASE-TX : Cat5 or later UTP (≤ 100 meter) 1000BASE-TX : Cat6 or later UTP (≤ 1000 meter)
LED Indicator	PWR: Power LED SYS:(System LED) 1~48:(Link LED=10/100M Link、1000M=Gigabit Link) 1~48:(PoE LED=PoE on) 25 26: (SFP LED)
Power	Built-in power AC 100~240V 50/60HZ MAX Max Current 5A Max Power 850W
Operating Temperature/Humidity	-20~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Physical size	Product size: 442mm*375mm*44mm approx Packing size: 515mm*375mm*95mm
N.W/G.W (kg)	3.5kg/4.3kg
Installation type	1U Rack type, 19 "
Lightning protection level	3KV 8/20us; IP30
Certificate	CE, LVD, RoHS
Warranty	3 year + 2 year extended at extra cost (Accessories not included)

Software Specification	
PoE management	PoE port switch
	PoE protocol type configuration
	PoE port restart
	PoE log function configuration
	PoE port status, current, power and voltage display
System state	Support system information display
	Support port exception protection display
	Support port bandwidth usage display
	Support link aggregation display
	Support static / dynamic MAC address table display
Network configuration	Support management IP address configuration
	Support system time configuration
Port	Support port status, rate and flow control configuration
	Support port mirroring
	Support port exception protection (BPDU / self ring, broadcast flooding, ACL, DHCP message speed limit, etc.)
	Support link 8 group aggregation
	Support IEEE configuration
	Support mega frame configuration
	Support port isolation configuration
VLAN	Support 4094 VLAN addresses
	Support 802.11Q VLAN, MTU VLAN, terminal VLAN
MAC	Support static MAC address table
	Support dynamic MAC address table
	Support MAC address transition table
Survival tree protocol	Support STP/RSTP/MSTP tree protocol
IGMP	Support IPv4 / IPv6 multicast forwarding
	Support IPv4 / IPv6 static routing
	Support IPv4 / IPv6 port restrictions
	IGMP snooping V1 / V2 / V3 supported
Security	Support management VLAN
	Support management and maintenance mode selection
QoS	Supports 8 port queues
	Support port priority, cos priority, 802.1p priority and DSCP priority
	Support port speed limit and exit queue speed limit
Equipment diagnosis	Support log function configuration
	Support remote log server configuration
	Support ping function
	Support traceroute test
	Support electrical port test
Equipment management	Support optical module information diagnosis
	Support user configuration
	Support web / TFTP / HTTP firmware upgrade
	Support profile import and export



AADONA Communication Pvt Ltd

Corporate Headquarters

1st Floor, Phoenix Tech Tower, Plot No.14/46,
IDA-Uppal, Hyderabad, Telangana 500039

www.aadona.com

Toll Free No. : 1800 202 6599
contact@aadona.com

AADONA Communication Pvt Ltd

Production, Warehousing and Billing Center

7, SBI Colony, Mohaba Bazar, Hirapur Road,
Raipur Chhattisgarh, 492099

www.aadona.com

Toll Free No. : 1800 202 6599
contact@aadona.com

AADONA and AADONA logo are trademarks of AADONA Communication Pvt Ltd Printed in India